


<b>Name of the Equipment / Facility</b>	<b>500 Kgs Shock Machine</b>																
<b>Purpose of Use</b>	To Simulate Shock Environment																
<b>Photograph</b>																	
<b>Key Specifications</b>	<p>!</p> <table border="1"> <thead> <tr> <th><u>PARAMETER</u></th> <th><u>MAIN SPECIFICATIONS</u></th> </tr> </thead> <tbody> <tr> <td>TYPE</td> <td>PNEUMATIC</td> </tr> <tr> <td>MODEL</td> <td>2424 (550) PA-PC - (250 Kg M/C) 1818 (550) PA-PC - (500 Kg M/C)</td> </tr> <tr> <td>TABLE SIZE &amp; WEIGHT</td> <td>600×600 mm &amp; 272 Kg - (250 Kg M/C)</td> </tr> <tr> <td>MAX. SPECIMEN SIZE</td> <td>1000×1000 (mm) &amp; 680 Kg - (500 Kg M/C) 600×600×1000 (mm) - (250 Kg M/C)</td> </tr> <tr> <td>MAXIMUM 'g'</td> <td>200 'g'</td> </tr> <tr> <td>PULSE DURATION (ms)</td> <td>3 to 50 milli seconds</td> </tr> <tr> <td>MAX. SPECIMEN WEIGHT</td> <td>Upto 250 Kg - (250 Kg M/C) Upto 500 Kg - (500 Kg M/C)</td> </tr> </tbody> </table>	<u>PARAMETER</u>	<u>MAIN SPECIFICATIONS</u>	TYPE	PNEUMATIC	MODEL	2424 (550) PA-PC - (250 Kg M/C) 1818 (550) PA-PC - (500 Kg M/C)	TABLE SIZE & WEIGHT	600×600 mm & 272 Kg - (250 Kg M/C)	MAX. SPECIMEN SIZE	1000×1000 (mm) & 680 Kg - (500 Kg M/C) 600×600×1000 (mm) - (250 Kg M/C)	MAXIMUM 'g'	200 'g'	PULSE DURATION (ms)	3 to 50 milli seconds	MAX. SPECIMEN WEIGHT	Upto 250 Kg - (250 Kg M/C) Upto 500 Kg - (500 Kg M/C)
<u>PARAMETER</u>	<u>MAIN SPECIFICATIONS</u>																
TYPE	PNEUMATIC																
MODEL	2424 (550) PA-PC - (250 Kg M/C) 1818 (550) PA-PC - (500 Kg M/C)																
TABLE SIZE & WEIGHT	600×600 mm & 272 Kg - (250 Kg M/C)																
MAX. SPECIMEN SIZE	1000×1000 (mm) & 680 Kg - (500 Kg M/C) 600×600×1000 (mm) - (250 Kg M/C)																
MAXIMUM 'g'	200 'g'																
PULSE DURATION (ms)	3 to 50 milli seconds																
MAX. SPECIMEN WEIGHT	Upto 250 Kg - (250 Kg M/C) Upto 500 Kg - (500 Kg M/C)																
<b>Representative Output (if Possible)</b>	Acceleration																